

MDT Interface, MDRC

Version		
SCN-LK001.03	Line Coupler with Data Secure	2SU MDRC

The **MDT Line Coupler** connects two KNX lines to each other. The MDT Line Coupler is a modular installation device for fixed installation in dry rooms. It fits on DIN 35mm rails in power distribution boards or closed compact boxes.

For project design and commissioning of the MDT Line Coupler it is recommended to use the ETS.

Please download the application software at www.mdt.de/Downloads.html

SCN-LK001.03



- Production in Engelskirchen, certified according to ISO 9001
- Line Coupler to connect two KNX lines to each other
- Separate bus power supply for each line required
- Filter functions to reduce bus load
- **Supports extended group addresses**
- **Supports KNX Data Secure (from ETS 5.7)**
- Quick application download (long frame support for ETS5/6)
- 3 years warranty

Technical Data	SCN-LK001.02		
Interface	KNX		
Specification KNX interface	TP-256		
Available application software	ETS 5/6		
Permitted wire gauge			
Screw terminal	--		
KNX busconnection terminal	0,8 mm Ø, solid core		
Power Supply	KNX bus		
Power consumption	< 0,3 W each line		
Operation temperature range	0 to +45 °C		
Enclosure	IP 20		
Dimensions MDRC (Space Units)	2SU		

Exemplary circuit diagram SCN-LK001.03



